

DUCKBACK®

P-3™ Peeling Paint Primer

4475
50 VOC



General Description

DUCKBACK® P-3 Peeling Paint Primer is a 100% acrylic exterior elastomeric stabilizing primer with advanced adhesive technology specifically designed to lock down old peeling paint. The glue-like adhesive properties of P-3™ Primer act as a super bonding agent for all top coat solid color paints and stains. The unique elastomeric technology of P-3™ Primer is capable of expanding up to 300% in hot temperatures and contracts when it is cold, remaining permanently flexible and breathable in all temperature and humidity conditions. P-3™ Primer resists most rust and tannin bleeding problems. P-3™ Primer is an excellent solution to old weathered peeling decks and siding surfaces, reducing the cost of painting by significantly extending the life of all latex paints and solid color stains.

Recommended Substrates

Use P-3™ Primer to stabilize new and problem peeling areas on wood decking and siding, concrete, stucco, rusty metal railings, rusty nail heads, and galvanized metal surfaces. Note: Not for use on garage floors, driveways, or automobile traffic areas.

Tinting & Base Color Information

Ready Mix. Do not tint.

SC 4475-Primer

Features / Benefits

- Stabilizes Peeling Paint
- Superior Bonding Agent
- Extends the life of extremely damaged, painted surface

Product Application

SURFACE PREPARATION:

All surfaces must be clean, dry, and free from dirt, mildew stains, dust and other foreign matter. Remove surface stains, dirt and failed oxidized stains with Superdeck® Wood Cleaner. For concrete use Mason's Select® Concrete Cleaner to clean surface. Remove loose peeling paint, rinse thoroughly with water and allow to completely dry before applying P-3™ Primer. For use over high sheen enamel type coatings roughen surface before using P-3™ Primer.

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

PRODUCT PREPARATION:

Shake well or stir thoroughly from bottom to top of container and occasionally during application. Test small area before doing entire job to ensure desired results.

THINNING:


Do not thin.

TINTING:

DO NOT TINT. P-3™ Primer dries to a light green shade to indicate where the product has been applied. Product is supplied ready to use.

APPLICATION METHODS:

Product may be applied by brush, roller, or airless sprayer. Use a nylon or polyester brush or a ½" to ¾" synthetic roller cover. Back rolling is suggested when spraying, working the product smoothly and evenly into the surface to ensure a uniform appearance. Apply 1–2 coats to stabilize area.



Product Application (cont.)

APPLICATION OF TOP COAT:

Do not apply oil base paints or stains over P-3™ Primer. Top coat P-3™ Primer only with a high quality 100% acrylic latex paint or solid color stain such as Superdeck® Acrylic Solid Color Stain. Top coat all horizontal decking within 24 hours and vertical siding within 48 hours. NOTE: PRODUCT REMAINS PERMANENTLY TACKY UNTIL TOP COATED AND MAY PICK UP DIRT AND DEBRIS IF NOT TOP COATED WITHIN THE RECOMMENDED TIME PERIOD.

NUMBER OF COATS:

1–2 coats are recommended.

APPLICATION TEMPERATURE:

45°F.–90°F. Do not apply if surface is hot to touch or if rain is likely to occur.

DRY TIME @ 77°F:

Allow 1–2 hours dry time between coats. Dry time to recoat will vary depending substrate, temperature, and humidity conditions.

SPREAD RATE:

250–350 sq. ft. per gallon. Spread rate will vary depending on porosity of substrate

CLEAN UP:

Clean brushes and equipment with soap and water.

Physical Properties

<i>MATERIAL:</i>	Acrylic Elastomeric
<i>DENSITY:</i>	9.16 lbs/gal
<i>pH:</i>	8.00–8.50
<i>COVERAGE:</i>	250–350 sq ft/gal
<i>DRY TIME:</i>	1–2 hours between coats
<i>VISCOSITY:</i>	90–95 KU
<i>TOTAL SOLIDS by WEIGHT:</i>	38%
<i>TOTAL SOLIDS by Volume:</i>	31.70%
<i>V.O.C.:</i>	Less than 50 grams/liter
<i>FLASH POINT:</i>	None
<i>ELONGATION % @ .008 inch:</i>	858%
<i>TENSILE STRENGTH @ .008 inch:</i>	106psi

OTHER:

SC 4475 P-3™ Peeling Paint Primer

<u>CAS Number</u>	<u>Ingredient</u>
7732-18-5	Water
Proprietary	Acrylic Polymer
12736-96-8	Nepheline Syenite
Proprietary	Calcium Barium Phospho Silicate

NON-PHOTOCHEMICALLY REACTIVE

VOC: 50 g/L - 0.42 lb/gal as per 40 CFR 59.406

Cautions

CAUTIONS: Contains **ANTIMONY**. Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.** Do not apply on toys and other children's articles or furniture.

01/14 (2416)

Conformance

OTC Approved:	Yes
SCAQMD Approved:	Yes
LADCO Approved:	Yes
CARB Approved:	Yes
Biodegradable:	No
ASTM Standard:	N/A
Master Painters Institute (MPI):	N/A

Packaging

1-Gallon Container - 124 fl oz (3⁷/₈ U.S. Qt) 3.66 L
5-Gallon Container - 620 fl oz (4²⁷/₃₂ U.S. Gal) 18.3 L

Limited Warranty

If this product, when applied according to label instructions to a properly prepared surface, fails to perform in accordance with applicable product literature, manufacturer shall, upon presentation of proof of purchase to manufacturer or its authorized representative, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, or failure of a previous product. This is your sole remedy under this warranty. To obtain performance under this warranty, contact manufacturer at (800) 825-5382 or

Limited Warranty (cont.)

superdeck.com. You may be asked to contact the retailer from whom you purchased this product for further warranty instructions. THIS WARRANTY EXCLUDES (1) LABOR OR COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state.

