

# SUPERDECK®

## 5200 Series Semi-Solid Stain with Cool Feel™ Technology 100 VOC



### General Description

- Provides an exterior IR semi-solid film
- Contains pigments that actually reflect solar rays back into the atmosphere, thereby helping reduce the exterior surface temperatures of decks exposed to the constant assault of direct sunlight
- Excellent penetration for protecting new horizontal exterior wood surfaces
- Can be applied to damp surfaces, allowing surface to be prepared and stained in one day
- This product contains agents which inhibit the growth of mildew on the surface of this stain film.

### Recommended Substrates

New or old exterior wood decking, boat docks, plywood decking, ramps, fences, rails, wood siding, balconies, porches, stairs, and walkways. Note: not for use on garage floors, driveways, or automobile traffic areas.

### Tinting & Base Color Information

Ready Mix Colors - Do Not Tint

- DPI-5201 - HAWTHORNE
- DPI-5202 - CEDAR BARK
- DPI-5203- CHESTNUT
- DPI-5204 - RIVERWOOD
- DPI-5205 - CHARWOOD
- DPI-5206 - BLUE SHADOW

### Features / Benefits

Helps reduce surface temperatures  
Reflects solar rays back into the atmosphere

### Product Application

#### **SURFACE PREPARATION:**

All surfaces must be clean, dry, and free from dirt, mildew stains, dust and other foreign matter. Do not apply over sealed surfaces. For wood surfaces remove surface stains, dirt and failed oxidized stains with Superdeck® Wood Cleaner. Remove all loose peeling paint, rinse thoroughly with water and allow to completely dry before coating. **WARNING!** Removal of old paint by sanding, scraping, or other means may generate dust or fumes that may contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

#### **PRODUCT PREPARATION:**

Shake well or stir thoroughly from bottom to top of container and occasionally during application. When using more than one container of product, intermix all containers to ensure color consistency. Test small area first for color satisfaction.

#### **THINNING:**

Do not thin.





## Conformance

|                  |     |
|------------------|-----|
| OTC Approved:    | Yes |
| SCAQMD Approved: | Yes |
| LADCO Approved:  | Yes |
| CARB Approved:   | Yes |
| CARB SCM 2007 :  | Yes |

## Packaging

1-Gallon Container - 128 fl oz 3.78 L

## Limited Warranty

If this product, when applied according to label instructions to a properly prepared surface, fails to perform in accordance with applicable product literature, manufacturer shall, upon presentation of proof of purchase to manufacturer or its authorized representative, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, or failure of a previous product. This is your sole remedy under this warranty. To obtain performance under this warranty, contact manufacturer at (800) 825-5382 or [superdeck.com](http://superdeck.com). You may be asked to contact the retailer from whom you purchased this product for further warranty instructions. **THIS WARRANTY EXCLUDES (1) LABOR OR COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state.

09/27 (16)

