

MASON'S SELECT® Concrete Cleaner

6500



General Description

MASON'S SELECT® CONCRETE CLEANER removes surface stains caused by dirt, grime, oil, grease, mildew and algae from concrete and masonry surfaces. Concrete Cleaner is fast acting and easy to use. Use Concrete Cleaner to neutralize surface after being etched.

Recommended Substrates

Exterior concrete and masonry surfaces.

Tinting & Base Color Information

Ready to use. Do not tint.

DB 6500

Features / Benefits

- Removes Dirt, Oil and Grease
- Neutralizes Concrete After Etching
- Concentrated Formula

Product Application

APPLICATION:

Shake well before using. Apply to damp or dry concrete using a brush, roller or pump-up sprayer. Use synthetic brushes or rollers only. For maximum effectiveness, keep Cleaner wet on surface by occasionally misting with water. Allow Cleaner to remain wet on surface for 15–30 minutes before scrubbing with a bristle brush or hard bristled broom. If contaminants are loose and the surface is ready, rinse entire area thoroughly with water using a garden hose or pressure washer.

PRODUCT DILUTION:

Maintenance Cleaning:

For mild cleaning mix ½ gallon of Cleaner with 3 ½ gallons of water.

Product Application (cont.)

General Cleaning:

Mix 1 gallon of product to 3 gallons of water.

Heavy Cleaning:

May require more than one application for extremely stained surfaces.

Coverage:

400–800 sq. ft. when one gallon of Cleaner is diluted with three gallons of water.

PRECAUTIONS:

Apply product at temperatures above 50°F. and below 90°F. Do not apply in direct sunlight if possible. Protect any aluminum surfaces (such as window frames) to prevent discoloration. Product will etch metal. If product makes contact with glass, rinse thoroughly before it dries. Mist any nearby vegetation with water before and after application.

SAFE USE AND STORAGE:


When using, do not eat, drink or smoke. Wash hands after use and before eating, drinking or smoking. Product is corrosive, avoid contact with metals such as aluminum. Do not transfer contents into a metal container or unlabeled container. Store in well ventilated area. Keep container tightly closed when not in use. Protect from freezing. For exterior use only.

Physical Properties

DB 6500 Concrete Cleaner

CAS Number	Ingredient
7732-18-5	Water
34590-94-8	2-Methoxymethylethoxypropanol
6834-92-0	Sodium Metasilicate Pentahydrate
1310-73-2	Sodium Hydroxide
13007-85-7	Sodium Glucoheptonate

NON-PHOTOCHEMICALLY REACTIVE
VOC: 583 g/L – 4.87 lb/gal as per 40 CFR 59.406



Cautions

DANGER! CAUSES EYE, SKIN AND RESPIRATORY TRACT BURNS. Before using, carefully read **CAUTIONS** section.

CAUTIONS: CONTAINS AMINE & SODIUM METASILICATE. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, do not induce vomiting. Call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

Packaging

1-Gallon Container - 124 fl oz ($3\frac{7}{8}$ U.S. Qt) 3.66 L

Limited Warranty

If this product, when applied according to label instructions to a properly prepared surface, fails to perform in accordance with applicable product literature, Duckback Products shall, upon presentation of proof of purchase to Duckback Products or its authorized representative, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, or failure of a previous product. This is your sole remedy under this warranty. To obtain performance under this warranty, contact Duckback Products at (800) 825-5382 or superdeck.com. You may be asked to contact the retailer from whom you purchased this product for further warranty instructions. THIS WARRANTY EXCLUDES (1) LABOR OR COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state.