

SUPERDECK® Log Home Oil Finish

7000 Series
350 VOC



General Description

SUPERDECK® LOG HOME OIL FINISH is a high solids, wood finish developed to give superior protection and beautiful color to your log home. It is specially formulated with the highest quality transparent oxide pigments to reflect harmful UV rays and a unique penetrating oil system to repel water. The product is also specially formulated to resist growth of mildew and algae on the coating's surface. Log Home Oil Finish offers the additional benefit of being resistant to foot traffic patterns on horizontal surfaces. Log Home Oil Finish is excellent for interior use and is compatible with chinking and caulks.

Recommended Substrates

For use on all exterior and interior, horizontal and vertical wood surfaces. For wood substrates only.

Tinting & Base Color Information

Log Home Oil Finish can be used as is or it can be tinted with up to 4 ounces of colorant per gallon. Tintable to 9 additional colors.

DB 7100-AMBER HUE
(Tints to Creekstone Gray, Cloud Gray, Mahogany)

DB 7200-GOLDEN HONEY
(Tints to Pecan, Evergreen, Teak)

DB 7300-AUTUMN BROWN
(Tints to Blonde Oak, Walnut Brown, Deep Forest)

Features / Benefits

- One Coat Coverage
- Maximum Grain Clarity
- For Interior & Exterior
- Use on Logs, Chinking, and Siding

Product Application

SURFACE PREPARATION:

All surfaces must be clean, dry, and free from dirt, mildew stains, dust and other foreign matter. Do not apply over sealed surfaces. Remove surface stains, dirt and failed oxidized stains with Superdeck® Wood Cleaner. Remove solid stains or paints with Superdeck® Wood Stripper. For redwood and cedar, follow cleaning or stripping with Superdeck® Wood Brightener to remove tannin stains and brighten wood to its original color. For new wood remove mill glaze with Superdeck® Wood Brightener.

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

PRODUCT PREPARATION:

Product should be shaken or stirred before and during application. When using more than one container of product, intermix all product and stir well to ensure color consistency.

THINNING:

Do not thin.

APPLICATION METHODS:

Product may be brushed, rolled or sprayed. If sprayed, use the lowest possible pressure needed for a reasonable spray pattern. Back rolling is suggested when spraying, working the product smoothly and evenly into the wood. This will decrease the possibility of pools or puddles on the surface and ensure a properly penetrated finish.



Product Application (cont.)

APPLICATION:

Proper application is essential in order to accomplish the full benefits of product appearance and performance. Different wood species, textures and natural color will affect finished shade. Always test a small area first for color satisfaction before coating entire project. Log Home Oil Finish is a penetrating stain that must be applied only at a rate the wood will absorb. Do not pool or puddle product on surface. Excess product allowed to sit on surface will result in a tacky finish and extended dry time. Remove tacky finish with mineral spirits within 24 hours of application or with a mild solution of Wood Cleaner after 24 hours. Follow manufacturer's instructions for safe use with solvents. When properly applied, the wood surface will have a positive dry and the wood fibers beneath the surface will maintain excellent lubrication. Thoroughly coat the porous ends of all boards with product.

NUMBER OF COATS:

One coat depending on wood porosity and wood moisture content.

APPLICATION TEMPERATURE:

40°F.–95°F. Do not apply if wood surface is hot to touch or if rain is likely to occur.

DRY TIME @ 77°F:

8 hours to touch, 24 hours for traffic; depending on weather conditions.

SPREAD RATE:

Approximate spread rate:

Smooth Surfaces: 250–350 sq. ft./gal.

Rough Sawn: 150–250 sq. ft./gal.

CLEAN UP:

Clean brushes and equipment with mineral spirits following product manufacturer's directions. Dispose of empty container or unused portion in accordance with local, state, and federal regulations.

Physical Properties

| | |
|--------------------|--|
| RESIN TYPE: | Tung Oil Linseed Oil Alkyd Resin |
| SOLVENT: | Mineral Spirits |
| PIGMENT: | Transparent Oxide |

Physical Properties (cont.)

| | |
|------------------------------|-------------------------------|
| LBS. PER GALLON: | 7.37–7.46 |
| SPECIFIC GRAVITY: | .88–.90 |
| SOLIDS (% BY WEIGHT): | 61% |
| V.O.C.: | Less than 350 grams per liter |
| FLASH POINT (T.C.C.): | 111°F. |

OTHER:

DB 7100 Log Home Oil Finish Amber Hue

| <u>CAS Number</u> | <u>Ingredient</u> |
|---|-------------------------|
| 8001-26-1 | Linseed Oil |
| 64742-88-7 | Mineral Spirits |
| 8001-20-5 | Tung Oil |
| Proprietary | Soya Alkyd Polymer |
| 111-76-2 | 2-Butoxyethanol |
| 136-52-7 | Cobalt 2-Ethylhexanoate |
| NON-PHOTOCHEMICALLY REACTIVE | |
| VOC: 349 g/L – 2.91 lb/gal as per 40 CFR 59.406 | |

DB 7200 Log Home Oil Finish Golden Honey

| <u>CAS Number</u> | <u>Ingredient</u> |
|---|-------------------------|
| 8001-26-1 | Linseed Oil |
| 64742-88-7 | Mineral Spirits |
| 8001-20-5 | Tung Oil |
| Proprietary | Soya Alkyd Polymer |
| 111-76-2 | 2-Butoxyethanol |
| 136-52-7 | Cobalt 2-Ethylhexanoate |
| NON-PHOTOCHEMICALLY REACTIVE | |
| VOC: 349 g/L – 2.91 lb/gal as per 40 CFR 59.406 | |

DB 7300 Log Home Oil Finish Autumn Brown

| <u>CAS Number</u> | <u>Ingredient</u> |
|---|-------------------------|
| 8001-26-1 | Linseed Oil |
| 64742-88-7 | Mineral Spirits |
| 8001-20-5 | Tung Oil |
| Proprietary | Soya Alkyd Polymer |
| 111-76-2 | 2-Butoxyethanol |
| 136-52-7 | Cobalt 2-Ethylhexanoate |
| NON-PHOTOCHEMICALLY REACTIVE | |
| VOC: 349 g/L – 2.91 lb/gal as per 40 CFR 59.406 | |



Cautions

DANGER! HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE! VAPOR HARMFUL. IRRITATES EYES, SKIN AND RESPIRATORY TRACT.

Before using, carefully read **CAUTIONS** on back panel.

CAUTIONS: Contains **ALIPHATIC HYDROCARBONS**. Contents are **COMBUSTIBLE**. Keep away from heat and open flame. **VAPOR HARMFUL**. Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use.

Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

01/10 (26)

Conformance

| | |
|----------------------------------|-----|
| OTC Approved: | No |
| SCAQMD Approved: | No |
| LADCO Approved: | No |
| CARB Approved: | No |
| Biodegradable: | No |
| ASTM Standard: | N/A |
| Master Painters Institute (MPI): | N/A |

Packaging

1-Gallon Container - 124 fl oz (3⁷/₈ U.S. Qt) 3.66 L

5-Gallon Container - 620 fl oz (4²⁷/₃₂ U.S. Gal) 18.3 L

Limited Warranty

If this product, when applied according to label instructions to a properly prepared surface, fails to perform in accordance with applicable product literature, manufacturer shall, upon presentation of proof of purchase to manufacturer or its authorized representative, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, or failure of a previous product. This is your sole remedy under this warranty. To obtain performance under this warranty, contact manufacturer at (800) 825-5382 or superdeck.com. You may be asked to contact the retailer from whom you purchased this product for further warranty instructions. THIS WARRANTY EXCLUDES (1) LABOR OR COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state.

