

SUPERDECK®

Exterior Wood Stripper

1460



General Description

SUPERDECK® WOOD STRIPPER is a ready to use solution that will remove paint, stains and varnishes from exterior wood. It is thick enough to use on vertical surfaces. After stripping, use SUPERDECK® Wood Brightener to neutralize the wood surface and restore the natural tone to wood.

Recommended Substrates

For all exterior wood.

Tinting & Base Color Information

Ready to use. Do Not Tint.

DB 1460

Features / Benefits

- Removes Old Coatings
- Ready to Use Formula
- Clings to Horizontal & Vertical Surfaces

Product Application

APPLICATION:

DO NOT DILUTE PRODUCT. Shake well before using. Spray wood with water, then apply Stripper with a brush or roller. Use synthetic brushes or rollers only. Wood Stripper's thick formula may be used on vertical surfaces. To maintain product effectiveness, keep Stripper wet on surface by occasionally misting with water. Allow Stripper to stay wet on surface approximately 15–45 minutes to remove coating. Difficult areas may take longer. Wood Stripper becomes extremely slippery once applied. Work on small enough areas to avoid walking on treated surface. Test a small area to determine the time required for product to strip effectively.

Product Application (cont.)

RINSING:

Test a small area by scrubbing with a bristle brush to determine if the coating is easily removed and the surface is ready for rinsing. When ready, scrub the surface with a firm bristle brush or long handled push broom. Rinse thoroughly with water using a garden hose. Rinse any residue from plants. After stripping, use SUPERDECK® Wood Brightener to neutralize the wood surface and restore the natural tone to wood.

BRIGHTENING:

Wood species such as redwood, cedar and fir will tend to darken after being stripped. Use Superdeck® Wood Brightener as the final step to brighten the wood and neutralize the surface before coating.

PRECAUTIONS:

Apply product at temperatures above 50°F. and below 90°F. Do not apply in direct sunlight if possible. Protect any aluminum surfaces (such as window frames) to prevent discoloration. Product will etch metal. If product makes contact with glass, rinse thoroughly before it dries. Mist any nearby vegetation with water before and after application.

COVERAGE:


100–200 sq. ft. per gallon

CLEAN UP:

Clean all tools with water.

SAFE USE & STORAGE:

When using, do not eat, drink or smoke. Wash hands after use and before eating, drinking or smoking. Product is corrosive, avoid contact with metals such as aluminum. Do not transfer contents into a metal container or unlabeled container. Store in well ventilated area. Keep container tightly closed when not in use. Protect from freezing. For exterior use only.



Physical Properties

DB1460 Exterior Wood Stripper

<u>CAS Number</u>	<u>Ingredient</u>
7732-18-5	Water
1310-73-2	Sodium Hydroxide
6834-92-0	Sodium Metasilicate Pentahydrate
1310-58-3	Potassium Hydroxide
13007-85-7	Sodium Glucoheptonate

NON-PHOTOCHEMICALLY REACTIVE
VOC: 0 g/L – 0.00 lb/gal as per 40 CFR 59.406

Cautions

CAUTIONS: Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Causes severe burns to eyes and mucous membranes on contact. Wear protective gloves. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water for 15 minutes. Get medical attention. For skin contact, wash thoroughly with soap and water. If irritation persists, get medical attention. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

01/10 (50)

Packaging

1-Gallon Container - 124 fl oz (3⁷/₈ U.S. Qt) 3.66 L

Product Guarantee

LIMITED WARRANTY: If this product, when applied according to label instructions to a properly prepared surface, fails to perform in accordance with applicable product literature, Duckback Products shall, upon presentation of proof of purchase to Duckback Products or its authorized representative, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, or failure of a previous product. This is your sole remedy under this warranty. To obtain performance under this warranty, contact Duckback Products at (800) 825-5382 or superdeck.com. You may be asked to contact the retailer from whom you purchased this product for further warranty instructions. THIS WARRANTY EXCLUDES (1) LABOR OR COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state.